

ProSeries™ HI Side & Top

THE RELIABLE AND COMPETITIVE SOLUTION

- **Polypropylene mold-injected filters**, for pools up to 65 m³
- **Hard-wearing and resistant to intense chemical treatments**
- **Top and side, valve and manometer included**
- **Easy maintenance:** transparent SAN® screw-on cover, easy opening, no tools needed, and laterals quick connect
- **Double-side diffuser** for optimal water spreading over the media
- **Wide Double drain:** water only 1" / water + media 1 1/4"
- **Filter manufactured in Europe**



ProSeries™ HI Side

ProSeries™ HI Top




6-position valve




180 mm diameter threaded opening for simpler maintenance operations



Circular base for perfect filter stability



Dimensions of HI Side filter



Dimensions of HI Top filter

Technical Specifications

Max. water temperature	50°C
Operating pressure	0.5 - 1.3 bar
Maximum pressure	2.0 bar
Connection	1.5"
Tank / Arms / Unions / Cover	PP/PP/ABS/SAN®, suitable for saltwater
Granulometry of filtration media	0.4 ÷ 0.8 mm

	Flow rate	Diameter Ø	In/Out	Filtration area	Empty weight	Sand	Dimensions					Item
							A	B	C	D	E	
PROSERIES™ HI SIDE	6 m³/h	400	1" ½	0.13 m²	10.5 kg	50 kg	266 mm	391 mm	651 mm	503 mm	453 mm	S160SIE
	9.5 m³/h	500	1" ½	0.19 m²	12.5 kg	100 kg	345 mm	470 mm	808 mm	503 mm	553 mm	S210SIE
	14 m³/h	600	1" ½	0.28 m²	15.5 kg	125 kg	391 mm	516 mm	891 mm	503 mm	653 mm	S240SIE
PROSERIES™ HI TOP	6 m³/h	400	1" ½	0.13 m²	10 kg	50 kg	720 mm	780 mm	922 mm	503 mm	453 mm	S160TIE
	9.5 m³/h	500	1" ½	0.19 m²	12 kg	100 kg	877 mm	937 mm	1079 mm	503 mm	553 mm	S210TIE
	14 m³/h	600	1" ½	0.28 m²	15 kg	125 kg	960 mm	1020 mm	1161 mm	503 mm	653 mm	S240TIE